CABLE GLANDS FOR SPECIAL APPLICATIONS

VariaPro FKM — Metr.

Material	Nickel plated brass
Seal	FKM
O-Ring	FKM
Protection	IP 68 – 10 bar within the specified clamping range
Operating Temperature	-20 °C – 180 °C (-4 °F – 356 °F)

RoHS EMC

// High resistance against the influence of acids and chemicals
// Integrated option for EMC connection
// Large clamping range due to reducer
// No twisting of inserts and cables



AG	⌀k mm	GL	H mm	mm Dome Nut	mm Body	Number
M 20 x 1,5	7,0 – 14,0	6	27	22	24	1.752.2000.50*
M 20 x 1,5	10,0 – 14,0	6	27	22	24	1.752.2000.51
M 25 x 1,5	11,0 – 18,0	7	29	27	30	1.752.2500.50*
M 25 x 1,5	14,5 – 18,0	7	29	27	30	1.752.2500.51
M 32 x 1,5	16,0 – 25,0	8	34	36	40	1.752.3200.50*
M 32 x 1,5	20,5 – 25,0	8	34	36	40	1.752.3200.51
M 40 x 1,5	21,0 – 32,0	8	40	46	50	1.752.4000.50*
M 40 x 1,5	26,5 – 32,0	8	40	46	50	1.752.4000.51

* Versions with removable reducers

Suitable accessories from page 73